

SPRAYRANGER

THE LGP SPRAYER

*'You don't have to sacrifice capacity
to beat compaction'*



... GET ON THE GROUND SOONER AND GAIN MORE AVAILABLE SPRAYING DAYS WITH THE LIGHTEST SP SPRAYER OF ITS SIZE ON THE MARKET...

- Choice of tank sizes from 1,500-3,000 litres and booms up to 24m
- High-torque engines of up to 173hp driving through automatic transmission: no hydrostatic drive
 - Full air suspension and air-over-oil operated in-board wet brakes
- Unladen weight from 4.55t (3,000-litre/24m model); 0.7m ground clearance on 11.2 x 42 rowcrops



Alanco

AGRICULTURAL LTD



If you're concerned about soil compaction, find yourself frustrated when you can't get on the land, but don't want to sacrifice spraying output by running a smaller machine, there is an alternative: the British-built Alanco Sprayranger.

At **4.55t unladen in 3,000-litre/24m format**, it's around 1.0t lighter than many comparable SP sprayers, yet that doesn't mean we skimp on spec: all Sprayrangers come standard with features such as 4WS, automatic transmission for superb traction and hill-climbing ability, 250 l/min diaphragm pump, air-operated steps and an air line. You can specify your machine with auto-steer and air suspension.

And if you think LGP sprayers suit only small farms, think again. We can build models to your specification in any size from **1,500-3,000 litres** with booms from **12-24m**.

Each Sprayranger is **tailor-made to order** at our Kent factory, and backed by personal service support from those who make the machines. If you're serious about your soil, talk to us.

SPRAYRANGER: You don't have to sacrifice capacity to beat compaction.



SPECIFICATION:

- Ford 173hp direct-injection common rail Tier III turbocharged/intercooled engine
- ZF electronically-controlled 10F/2R automatic transmission c/w central locking diff
- Hydrostatic steering with four-wheel drive and
- 550/45 R22.5 or 560/65 R22.5 flotation tyres; 11.2x42 rowcrops (0.7m clearance)
- Luxuriously-appointed cab with air-suspended seat, carbon filtered fresh air ventilation, heating, air conditioning, Bluetooth CD/radio
- 1,500, 2,500 or 3,000-litre stainless tanks c/w integral clean water tank, self-fill suction point, tank wash kit, flushable pressure filter, auto flow rate controller
- 250 l/min piston diaphragm pump suitable for liquid fertiliser
- 12-24m four-section booms with recirculation, DCV triplex bodies supplied with set of Hypro Kematal jets, with auto shut-off and section control
- Air-operated cab steps and air line point for cleaning, inflation etc.

Alanco Agricultural Ltd,
Pattenden Lane, Marden,
Kent, TN12 9QT Tel: 01622 832830
info@sprayranger.co.uk

Twitter: @sprayranger
Facebook: Alanco Sprayranger
Web: info@sprayranger.co.uk



'GET ON THE GROUND SOONER AND GAIN MORE AVAILABLE SPRAYING DAYS WITH MINIMAL SOIL DISTURBANCE. ALANCO SPRAYRANGER: THE LGP SPRAYER'